

Beyondtech PureOptics™ Fiber NAP Boxes

Order Code: BTFAT0411B

In the era of lightning-fast communication and seamless connectivity, the Fiber Optics NAP (Network Access Point) Box stands as a beacon of innovation, empowering homes and businesses with unparalleled access to the digital world. Designed with precision engineering and cutting-edge technology, this NAP Box is the cornerstone of Fiber-to-the-Home (FTTH).

FEATURES AND BENEFITS

- Seamlessly integrates into existing FTTH networks for hassle-free setup.
- Adaptable architecture allows for easy upgrades to meet evolving demands.
- This distribution box accommodates up to 8 fiber optic cables, providing dedicated slots for splitters and accommodating up to 8 fusions. With provision for 8 SC adapters and designed for indoor use, it stands as an ideal, cost effective solution for FTTx networks.
- Separation design for splice and splitter use, high quality plastic construction, internal turnover structure, accommodates 8 SC adapters and tube-type splitters, supports up to 8 drop cables, IP65 protection.



SPECIFICATIONS

Applications:

Indoor/ Outdoor use: Splicing / Splitter

IN/OUT Ports:

2:8 / 3:8

Inlet/Outlet Caliber:

12 mm / Drop-3.0 mm

Max. Splice Capacity:

MAX: 8

Dimensions (H*W*D):

243 mm * 195 mm * 55 mm

Operating Temperature:

-40 °C to +65 °C

Package Contents:

- Fusion splice protection sleeves, Tie wraps, screws, universal plug, key to unlock.

A	B	C	D	E	F	G	H	I
BT	N	A1	1	6	0	0	0	B

Example: BTNA116000B = Beyondtech | FAT | Model A1 | 1 In | 6 Out | 0 Oval | 0 Splitter | 0 Connectors | Black

<p>A</p> <p>Beyondtech</p>	<p>B</p> <p>Box Family: N Fiber Access Terminal M Multi Service Terminal Closure</p>	<p>C</p> <p>Model Type: A1 / A2 / A3 / A4 / B1 / G2 / M2 / M4 / M6 / M8</p>										
<p>D</p> <p>In Ports Capacity: 0 / 1 / 2 / 3 / 4 / 5</p>	<p>E</p> <p>Out Ports Capacity: 0 / 2 / 3 / 4 / 5 / 6 / 7 / 8 / 12 / 16 / 24 / 32 / 64 / 128</p>	<p>F</p> <p>Cable Oval Entry Ports: 0 / 1 / 2</p>										
<p>G</p> <p>Splitter Capacity: 0 / 2 / 4 / 6 / 8 / 12 / 16 / 24 / 32</p>	<p>H</p> <p>Connectors Type:</p> <table border="0"> <tr> <td>0 None</td> <td>LCUD LC/UPC - D</td> </tr> <tr> <td>SCAS SC/APC - S</td> <td>LCAS LC/APC - S</td> </tr> <tr> <td>SCUS SC/UPC - S</td> <td>LCUS LC/UPC - S</td> </tr> <tr> <td>SCPS SC/PC - S</td> <td></td> </tr> <tr> <td>LCAD LC/APC - D</td> <td></td> </tr> </table>	0 None	LCUD LC/UPC - D	SCAS SC/APC - S	LCAS LC/APC - S	SCUS SC/UPC - S	LCUS LC/UPC - S	SCPS SC/PC - S		LCAD LC/APC - D		<p>I</p> <p>Color:</p> <p>B Black W White G Green</p>
0 None	LCUD LC/UPC - D											
SCAS SC/APC - S	LCAS LC/APC - S											
SCUS SC/UPC - S	LCUS LC/UPC - S											
SCPS SC/PC - S												
LCAD LC/APC - D												

Materials: **ABS, PCB, PC**
 IP Grades: **55 / 56 / 57 / 65 / 66 / 68**

Other options are available.
 Ask your Beyondtech sales representative.

Custom cabling per request



For more information on Beyondtech Premium Warranty, visit beyondtech.us/warranty



DISCLAIMER

This datasheet is from authorship and exclusive property of Beyondtech. His reproduction is banned in the integral or partially without mentioning his authorship, as well as the alteration of his content or context.

IMPORTANT NOTICE

All statements, technical information, and recommendations related to Beyondtech products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in Beyondtech current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of Beyondtech.



Order Code: BTFAT0411B

Type: Fiber NAP Boxes

Application: Indoor/ Outdoor use: Splicing / Splitter

IN/OUT Ports: 2:8 / 3:8

Inlet/Outlet Caliber: 12 mm / Drop-3.0 mm

Max. Splice Capacity: MAX: 8

Dimensions (H*W*D): 243 mm * 195 mm * 55 mm

Operating Temperature: -40 °C to +65 °C

WORLDWIDE CORPORATE HEADQUARTERS

Beyondtech INC
Miami, FL, USA
info@beyondtech.global
+1 (305) 897.3507

Beyondtech EUROPE
Madrid, ES
hola@beyondtech.es
+34 (911) 233.074

Rediret UK LTD.
London UK.
info@rediret.com
+44 (020) 3289.1190

For more information, visit our website
www.beyondtech.global, contact us
at customer@beyondtech.global or
call +1 (844) 283.5266 (toll-free).